

DogBone Dry Inlay


EPC Class 1 Gen 2, ISO 18 000-6C

Impinj Monza 4D

Sales code 3001873

Mechanical dimensions

A1 x A2	Antenna size	85,9 x 24 mm	± 0,5 mm	3,382 x 0,945 in
C	Web width	97 mm	± 0,5 mm	3,819 in
D	Pitch, length per piece MD	30 mm	± 0,5 mm	1,181 in
E	Antenna to web edge	5,6 mm	± 1,0 mm	0,220 in



Electrical characteristics

Integrated Circuit (IC)	Impinj Monza 4D
Air interface protocol	EPC Class 1 Gen 2, ISO 18 000-6C
Operation frequency	860 - 960 MHz
Memory	128 bit EPC plus 32 bit


General characteristics of transponder

Operating temperature (electronics parts)	-40 °C / +85 °C	-40 °F / 185 °F
ESD voltage immunity	± 2 kV peak HBM	
Shelf life: From the date of manufacture 2 years in	+20 °C, 50 % RH	68 °F, 50 % RH
Bending diameter (D)	> 50 mm, tension less than 10 N	

Delivery form

Transponder format	Continuous 1-wide
Transponder face material	Clear PET 12
Transponder antenna material	Aluminum
Final inspection	100 %, known faulty ones marked
Minimum delivery yield	97 %
Reel label	Reel number, Material number, Material description, Yield, qty of functional inlays, qty of non-functional inlays, date, time

Structure



Delivery details

Appearance	Single row reel form
Reel core	Card board core, inner diameter 76 mm (3 in)
Winding of the reel	Face out
Reel size	10000 pcs/reel Diameter: < 305 mm
Package size	10000 pcs/box Deliveries only in full packages.

Disclaimer:

SMARTRAC reserves the right to change its products and services at any time without notice. Our recommendations are based on our best knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage that may be caused when using the product. Use extra care in handling the product.

This technical specification replaces all earlier ones.

Version 4
 Update date 1 March 2012
 Author SMARTRAC / k731743
 Approved SMARTRAC / 01.03.2012 k036052

