

HF 38 x 22,5 mm Inlay


ISO 15 693, ISO 18 000-3 Mode 1

NXP ICode SLIX2

Sales code 3006460

Mechanical dimensions

A1 x A2	Antenna size	38 x 22,5 mm	± 0,5 mm	1,496 x 0,886 in
C	Web width	48 mm	± 0,5 mm	1,890 in
D	Pitch, length per piece MD	33 mm	± 0,5 mm	1,299 in
K	Antenna to web edge	5 mm	± 1,0 mm	0,197 in
M	Maximum Interleaf width	18 mm		0,709 in
N	Interleaf edge to IC	5 mm	± 2,5 mm	0,197 in
I	Minimum size of register mark (width x length)	5x3 mm		0,197 x 0,118 in
Q1	Antenna to etched register mark	3,75 mm	± 1,0 mm	0,148 in
	Thickness of the IC	127 µm	± 15 %	
Q2	Etched register mark to web edge	0,5 mm	± 0,5 mm	0,020 in
	Overall thickness of the transponder package (excluding IC and siliconized paper)	86 µm	± 10 %	



Electrical characteristics

Integrated Circuit (IC)	NXP ICode SLIX2
Air interface protocol	ISO 15 693, ISO 18 000-3 Mode 1
Operation frequency	13,56 MHz
Unloaded resonance frequency	TBD
Memory	2.5k bits user memory


General characteristics of transponder

Operating temperature (electronics parts)	-40 °C / +85 °C	-40 °F / 185 °F
ESD voltage immunity	± 2 kV peak HBM	
Shelf life: From the date of manufacture 2 years in	+20 °C, 50 % RH	68 °F, 50 % RH
Bending diameter (D)	> 50 mm, tension less than 10 N	

Delivery form

Transponder format	Continuous 1-wide
Transponder face material	No face
Transponder backing material	PET
Transponder antenna material	Aluminum, crimped coil
Final inspection	100 %, known faulty ones marked
Minimum delivery yield	97 %
Reel Label	Reel number, Material number, Material description, Yield, Qty of functional inlays, Qty of non-functional inlays, Date
Printability	Needs to be tested by customer

Structure



Delivery details

Appearance	Single row reel form
Reel core	Paper core inner diameter 76 mm (3 in)
Transponder alignment	Chip at rear of transponder
Winding of the reel	Face out
Package size	10000 pcs/box Deliveries only in full packages.

Disclaimer:

SMARTRAC reserves the right to change its products and services at any time without notice. Our recommendations are based on our best knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage that may be caused when using the product. Use extra care in handling the product.

This technical specification replaces all earlier ones.

Version	1
Update date	20 February 2017
Author	SMARTRAC /
Approved	SMARTRAC / 21.2.2017 Mervi Väisänen/Smartrac

